## **Amendments to the Claims:**


This listing of claims will replace all prior versions, and listings, of claims in this Application:

## **Listing of Claims**:

- 1) (Canceled).
- 2) (Previously Presented) A formulation according to claim 23, wherein the hectorite is selected from the group consisting of calcium hectorite and sodium hectorite.
- 3) (Previously Presented) The formulation according to claim 23, wherein the hectorite is sodium hectorite.
- 4) (Canceled).
- 5) (Previously Presented) The paint formulation according to claim 23, wherein the phosphonate additive is selected from the group consisting of:
  - a) Phosphonic acid compounds that contain at least two moieties having the structure:

and salts thereof,

b) Phosphinic acid compounds that contain at least two moieties having the structure:



and salts thereof, and

c) Compounds which form phosphoric or phosphonic acids, or salts thereof.

- 6) (Previously Presented) The paint formulation according to claim 23, further comprising an alkali swellable-rheological additive.
- 7) (Currently amended) The formulation according to claim 23 wherein the hectorite is sodium hectorite and the phosphonate compound is selected from the group consisting of:
  - a) Diphosphonic acids of formula R<sup>1</sup>R<sup>2</sup>C(PO(OH)<sub>2</sub>)<sub>2</sub>,
  - b) Diphosphonic acids of formula R<sup>1</sup>-CR<sup>2</sup>(PO(OH)<sub>2</sub>)-R<sup>3</sup>-CR<sup>2</sup>PO(OH)<sub>2</sub>-R<sup>5</sup>,
  - c) Phosphonic acids with general formula R<sup>1</sup>R<sup>4</sup>C=C(PO(OH)<sub>2</sub>)<sub>2</sub>, and
- d) The lithium, sodium, potassium, calcium and magnesium salts of the compounds described under a), b) and c),

where  $R^1$  can <u>is</u> be selected from the group <u>comprising consisting of H</u>, a linear or branched alkyl, alkene, hydroxyalkyl, aminoalkyl, hydroxyalkene, aminoalkene with 1 to 22 carbon atoms of <u>and</u> an aryl, hydroxyaryl, aminoaryl with 6 to 22 carbon atoms;  $R^2$  can be is selected from the group <u>comprising consisting of R</u><sup>1</sup> and OH;  $R^3$  is an alkyl with 0 to 22 carbon atoms; and both  $R^4$  and  $R^5$  can be is selected from the group  $R^1$ .

- 8) (Previously Presented) The formulation according to claim 23, wherein the phosphonate additive is selected from the group consisting of 1-hydroxyethylene-1,1-diphosphonic acid sodium salt or an ester thereof.
- 9) (Original) The formulation according to claim 8, wherein the hectorite is sodium hectorite.
- 10) (Currently amended) The paint formulation of claim 23 wherein the hectorite clay comprises about 0.1 to 10 wt. % hectorite clay; and the one or more phosphonate additives comprise about 0.5 to 6 wt % based on the weight of the hectorite clay.
- 11) (Original) The paint formulation according to claim 10, wherein the hectorite is selected from the group consisting of calcium hectorite and sodium hectorite and the formulation contains a rheological additive.
- 12) (Original) The paint formulation according to claim 10, where the phosphonate additive is selected from the group consisting of a 1-hydroxyethylene-1,1-diphosphonic acid, a salt thereof and an ester thereof.

13) (Currently amended) A method of making an automotive metallic paint formulation comprising:

- a) treating beneficiated or unbeneficiated natural hectorite with one or more phosphonate additives; and
- b) adding the treated <u>beneficiated or unbeneficiated natural hectorite</u> mixture to a paint formulation which comprises metallic flakes.
- 14) (Currently amended) The A method of making automotive metallic paint formulations elaim 13 comprising:
  - a) treating a mixture of hectorite and water with the one or more phosphonate additives to form a clay slurry; and
  - b) drying the resultant treated mixture; and
  - c) adding the dried treated mixture to the paint formulation which comprises the metal flakes.
- 15) (Canceled)
- 16) (Previously Presented) The method of claim 13 comprising:adding the treated mixture to the paint formulation as a pregel in water.
- 17) (Previously Presented) The method according to claim 16, wherein the phosphonate additive is 1-hydroxyethylene-1,1-diphosphonic acid tetra sodium salt.
- 18) (Canceled)
- 19) (Canceled)
- 20) (Canceled)
- 21) (Canceled)
- 22) (Previously Presented) The metallic paint formulation of claim 23 further comprising an alkali swellable rheological additive.
- 23) (Currently amended) An automotive metallic paint formulation comprising:
  - a) at least 0.1% of beneficiated or unbeneficiated natural hectorite clay;
  - b) from about 0.5 to 15 wt. %, based on the weight of the clay, of one or more phosphonate additives;

c) metallic flakes selected from the group consisting of aluminum, copper and mixtures thereof; and

- d) water.
- 24) (Previously Presented) A metallic paint formulation prepared by the process of claim 16.
- 25) (Currently amended) The method of claim 13 wherein the <u>beneficiated or unbeneficiated</u> natural hectorite and <u>clay</u> phosphonate <u>additives</u> and <u>water</u> are added as a post-correction additive.
- 26) (Original) The metallic paint formulation of claim 23 further comprising an alkali swellable chemical.
- 27) (Previously Presented) A metallic paint formulation prepared by the process of claim 13.
- 28) (Cancelled)
- 29) (Currently amended) The sprayable metallic paint formulation of claim 283 prepared by a process wherein the clay, phosphonate and water were are added to the metallic paint formulation as a pregel.
- 30) (Currently amended) The sprayable metallic paint formulation of claim 283 prepared by a process wherein the clay, phosphonate and water were are added to the metallic pain formulation as a post-correction additive.
- 31) (Currently amended) The sprayable metallic paint formulation of claim 28 23 further comprising an alkali swellable chemical.
- 32) (Currently amended) The sprayable-metallic <u>paint</u> formulation of claim <u>28</u> <u>23</u> prepared by a process wherein the clay and the phosphonate additive <u>were are</u> added to the formulation as a mixture.
- 33) (Currently amended) The paint formulation of claim 5 wherein the phosphonate additive is selected from the group consisting of lithium, sodium, potassium, calcium and magnesium salts of the compounds described under (a), (b) and (c).